



REVISION NOTE	DATE	SIGNATURE	CHECKED
A/0 RELEASED	05/11/14	黄得进	

Notes:

- Electrical**
- Voltage:50V AC(RMS)/DC
- Current:0.5A AC(RMS)/DC
- Contact Resistance:90mΩ max
- Insulation Resistance:500MΩ min
- Dielectric Withstanding Voltage:150V AC/RMS
- Operating Temp:-20℃~+85℃
- Materials**
- Housing:High temperature Plastic
- UL 94V-0
- Terminal:Copper Alloy

No. of Contacts	Dimensions			
	A	B	C	D
10 (2*5)	5.7	4.8	3.2	4.9
12 (2*6)	6.5	5.6	4.0	5.7
14 (2*7)	7.3	6.4	4.8	6.5
16 (2*8)	8.1	7.2	5.6	7.3
18 (2*9)	8.9	8.0	6.4	8.1
20 (2*10)	9.7	8.8	7.2	8.9
24 (2*12)	11.3	10.4	8.8	10.5
26 (2*13)	12.1	11.2	9.6	11.3
28 (2*14)	12.9	12.0	10.4	12.1
30 (2*15)	13.7	12.8	11.2	12.9
32 (2*16)	14.5	13.6	12.0	13.7
50 (2*25)	21.7	20.8	19.2	20.9

ITEM REF	QUANTITY	SEE NOTES	PART NUMBER
DESIGNED Kavith	06/01/12	CHECKED	50308031022YX
APPROVED			UNIT mm
SCALE			1:1

ITEM: 0.8mm BT08侧插型公座 (普通导柱)

DESIGNED: Shenzhen WenZhangJiMei technology co., LTD

CHECKED: 黄得进

APPROVED: 黄得进

SCALE: 1:1

UNIT: mm

PART NUMBER: 50308031022YX

DATE: 06/01/12

REVISION: A/0

深圳市文章济美科技有限公司

Shenzhen WenZhangJiMei technology co., LTD

DRAWING NUMBER

EDITTON

SHEET

A/1

1/1